

miniBOOSTER Hydraulic Intensifiers HC2W

Your Trusted Partner for Offshore Engineering,
Equipment Rental, Personnel & Ship Agent Services



The HC2W is a compact stainless-steel unit weighing only 1.0 kg. It is ideal for use in a variety of applications where building and maintaining high pressure is required. The HC2W raises supplied pressure to a higher outlet pressure and automatically compensates for consumption to maintain the high pressure.

Adjustment of the outlet pressure is carried out by varying the supplied pressure.

1:2 and 1:4 intensifiers are standard stock. But intensifiers with 11 different factors can be supplied in this series.

Hydraulic Intensifiers 1:2 & 1:4



E-mail: post@sagasubsea.no | Tel: +47 52-SUBSEA (52 78 23 32) | +47 906 94 490

miniBOOSTER Hydraulic Intensifiers HC2W

Technical specifications:

Inlet Pressure:	20-200 Bar
Max outlet pressure:	800 Bar
Return Pressure	As low as possible (to tank)
B Model:	With dump valve.
Weight:	1 kg.
Length (Without Fittings):	110 mm.
Body OD:	50 mm.
Material:	Stainless Steel.



E-mail: post@sagasubsea.no | Tel: +47 52-SUBSEA (52 78 23 32) | +47 906 94 490

Hydraulic Intensifiers 1:2 & 1:4

