

ROV Dredger Hoses

Your Trusted Partner for Offshore Engineering,
Equipment Rental, Personnel & Ship Agent Services



We have in stock Suction/Exhaust hoses for several size ROV Dredgers. We have as standard 4, 6, 8, and 10" Hoses in stock at Killingøy Offshorebase. The Arizona Superelastic hose is well proven hose, that Saga Subsea have used over a decade. Smaller dimensions for Super Zipjet pumps are also available upon request.

ROV Dredger Hoses

General Technical Data:	
Standard Dimension:	Ø: 4, 6, 8, and 10inch
Product Range:	1inch to 12inch (all dimensions can be delivered upon request)
Weight:	4inch: 2,7 kg/meter 6inch: 5 kg/meter 8inch: 9,5 kg/meter 10inch: 13,5 kg/meter
Inner Diameter:	4inch: 101,6 mm 6inch: 152,4 mm 8inch: 203,2 mm 10inch: 254 mm
Outer Diameter:	4inch: 116,2 mm 6inch: 170,4 mm 8inch: 229 mm 10inch: 283 mm
Bend Radius:	4inch: 400 mm 6inch: 610 mm 8inch: 800 mm 10inch: 1000 mm
Vacum:	9 m/H2O
Pressure Range:	4inch: 9 Bar 6inch: 6 Bar 8inch: 4,5 Bar 10inch: 4,5 Bar
Length:	Delivered in requested length. Standard lengths up to 50 meters.

E-mail: post@sagasubsea.no | Tel: +47 52-SUBSEA (52 78 23 32) | +47 904 00 631